

Barrier Fluid E

Synthetic barrier fluids



Your benefits at a glance

- Excellent low temperature fluidity
- High temperature stability property
- Ability to efficiently transfer heat

Your requirements - our solution

Summit Barrier Fluid E is formulated from the highest quality synthetic base stocks and fortified with additives to provide a non-reactive, oxidatively stable fluid for seal service over an extremely wide temperature range. This fluid has an excellent low temperature fluidity and high temperature stability property, as well as the ability to efficiently transfer heat and keep seal face cool. Summit Barrier Fluid E does not contain components that are known catalyst

poisons, and are compatible with most commonly used seal materials.

This lubricant is NSF Registered and meets USDA 1998 (H1) guidelines (lubricants with incidental food contact) for use in food plants. Summit Lubrication is an ISO 21469 certified facility. Do not add directly to food.

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	BARRIER FLUID E
Article number	340012
Demulsifying capacity	40/40/0 (10) (min)
Density	0.816 g/cm ³
Flash point	232 °C
Kinematic viscosity, 100°C	5.9 mm ² /s
Kinematic viscosity, 40°C	31.0 mm ² /s
Viscosity index	138
Copper corrosion, DIN EN ISO 2160, 3 h, 100°C	1 - 100 - 3 corrosion degree
Pour point	-61 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

Barrier Fluid E

Synthetic barrier fluids



Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsummit.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.