

Barrier Fluid Series

Synthetic barrier fluids



Your benefits at a glance

- Excellent low temperature fluidity
- High temperature stability property
- Ability to efficiently transfer heat

Your requirements - our solution

Summit Barrier Fluid Series lubricants are formulated from the highest quality synthetic base stocks and fortified with additives to provide a non-reactive, oxidatively stable fluid for seal service over an extremely wide temperature range. These fluids have excellent low temperature fluidity and high temperature stability properties, as well as the ability to efficiently transfer heat and keep the seal face cool. Summit's Barrier Fluid Series lubricants do not contain components that are known catalyst poisons, and are compatible

with most commonly used seal materials. Barrier Fluid 5 is environmentally safe and readily biodegradable according to OECD 301 B. Barrier Fluid Series products are NSF Registered and meet USDA 1998 (H1) guidelines (lubricants with incidental food contact) for use in food plants. Do not add directly to food. Summit is an ISO 21469 certified facility.

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	BARRIER FLUID 5	BARRIER FLUID 17	BARRIER FLUID 30	BARRIER FLUID 46
Article number	340011	340010	340272	340273
Demulsifying capacity	40/40/0 (10) (min)	40/40/0 (10) (min)	40/40/0 (10) (min)	40/40/0 (10) (min)
Density	0.796 g/cm ³	0.818 g/cm ³	0.825 g/cm ³	0.83 g/cm ³
Flash point	160 °C	200 °C	220 °C	200 °C
Kinematic viscosity, 100°C	1.7 mm ² /s	3.9 mm ² /s	5.9 mm ² /s	7.8 mm ² /s
Kinematic viscosity, 40°C	5.1 mm ² /s	16.9 mm ² /s	30.5 mm ² /s	46.0 mm ² /s
Viscosity index	-	127	141	139
Copper corrosion	1 - - corrosion degree			
Pour point	-75 °C	-73 °C	-61 °C	-41 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months	36 months	36 months	36 months

Characteristics	BARRIER FLUID 68
Article number	340274
Demulsifying capacity	40/40/0 (10) (min)
Density	0.834 g/cm ³

Barrier Fluid Series

Synthetic barrier fluids



Characteristics	BARRIER FLUID 68
Flash point	250 °C
Kinematic viscosity, 100°C	10.0 mm ² /s
Kinematic viscosity, 40°C	66.0 mm ² /s
Viscosity index	136
Copper corrosion	1 - - corrosion degree
Pour point	-57 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsummit.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.