

CO-120FG Extreme

High-temperature food grade chain oil



Your benefits at a glance

- Good wetting properties
- Excellent penetration with high dispersion stability

Your requirements - our solution

CO-120FG Extreme is a synthetic high-temperature food grade chain oil built to excel in extreme conditions. White solid lubricants are used in place of graphite solutions, which helps to improve food safety and avoid the contamination that comes with black particles. CO-120FG Extreme is used to lubricate chains operating at temperatures up to 1,202 °F. It also offers good wetting properties and excellent penetration with high dispersion stability.

CO-120FG Extreme chain oil can be used for the lubrication of transport chains operating in the food processing industry at very high temperatures, e.g. plate carrier chains in baking ovens, commonly found in bread, tortilla and pizza production lines.

Application

Transport chains operating in the food processing industry at very high temperatures.

Application notes

CO-120FG Extreme should always be shaken or agitated before use to make certain the white solid lubricants are in suspension.

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	CO-120FG EXTREME
Article number	340428
Density	1.04 g/cm ³
Flash point	220 °C
Kinematic viscosity, 100°C	20.0 mm ² /s
Kinematic viscosity, 40°C	120 mm ² /s
Viscosity index	190
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	24 months

CO-120FG Extreme

High-temperature food grade chain oil



Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsupport.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.