

EnviroTech® CO FG Series

High temperature chain lubricant



Your benefits at a glance

- Does not contain VOCs
- Contains a natural self-cleaning property
- Provides excellent protection against wear, rust, oxidation and corrosion

Your requirements - our solution

EnviroTech CO FG Series chain lubricants are specially developed, food grade chain lubricants blended from biosynthetic base oils and fortified with synthetic food grade white graphite. This unique high temperature formula lubricates at operating temperatures exceeding 1000°C and meets U.S.D.A. 1998 (H1) guidelines for applications where incidental food contact is possible. It does not contain VOCs and will out-perform other lubricants containing molybdenum disulfide, black graphite, or Teflon®. In addition, EnviroTech CO FG contains a natural self-cleaning property which cleans the buildup on chains attributable to the use of inferior chain lubricants. This superior chain lubricant provides excellent protection against wear, rust, oxidation, and corrosion.

Application

Use EnviroTech CO FG Series for chains exposed to high service temperatures which exceed those recommended for conventional lubricants. This product is ideal for oven chains used in plants which produce bread, cookies, cakes and other baked food products. It is also suitable for can making where decorative coatings are being cured or applied. EnviroTech CO FG can also be used in non-food grade high temperature applications.

Application notes

Special Instructions:

Because of the high concentration of white graphite in this chain oil, it needs agitation before use to ensure even distribution of the solid lubricant. The white graphite has proven to stay in suspension for up to two weeks after being introduced into a capability tube supplying lubricant to an applicator.

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	EnviroTech CO-68 FG	Envirotech CO-150 FG
Article number	340263	340248
Density	0.89 g/cm ³	0.9 g/cm ³
Fire point	335 °C	338 °C
Flash point	300 °C	296 °C
Kinematic viscosity, 100°C	12.5 mm ² /s	24.9 mm ² /s
Kinematic viscosity, 40°C	67.5 mm ² /s	147 mm ² /s
Viscosity index	187	203
Steel corrosion	passed	passed
Pour point	-28 °C	-25 °C
Four-ball tester: wear characteristics	0.40 mm	0.40 mm
Four-ball tester, welding load	160 kgf	160 kgf

EnviroTech® CO FG Series

High temperature chain lubricant



Characteristics	EnviroTech CO-68 FG	Envirotech CO-150 FG
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months	36 months

Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsummit.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.