

# NGP® Series

Natural gas compressor lubricant



## Your benefits at a glance

- The high viscosity index (V.I.) of NGP Series is comparable to a synthetic PAO and means a significant increase in operating temperature range over most mineral based oils. It also means a lower viscosity grade NGP Series product may be used in place of a higher viscosity mineral oil with a lower viscosity index. This can mean lower temperature flow limits and may eliminate the need for heated, pressurized day tanks and heat traced lines. It can also mean better lubricant film strength at higher cylinder and packing temperatures on reciprocating compressors.
- The pour point of NGP Series approaches that of a synthetic PAO and may be as much as 25 °F lower than some mineral based oils. The lower limit may eliminate no flow shutdowns on cold days or the need for special tank and line heaters.
- NGP Series is made from highly purified petroleum oils that only contain trace amounts of sulfur and other impurities found in group 1 mineral oils. Impurities common to many mineral oil base stocks can react with components of the gas stream to form by-products harmful to the compressor system.
- NGP Series is formulated to inhibit against the corrosive effects of wet CO<sub>2</sub> and H<sub>2</sub>S often found in gas compressor applications.

- NGP Series is tailor made for gas compressor applications It is not simply an R&O oil developed for general purpose lubrication put into gas compressor service. Both synthetics and petroleum based oils have their place in gas compressor applications. Consult with Summit's Gas Compressor Specialist to find out which product is right for your application.

## Your requirements - our solution

When a synthetic oil is needed, Summit's NGP Series highly refined petroleum based lubricants is formulated to provide some of the same benefits provided by hydrocarbon based synthetics such as PAO and PIB. The additive technology used in NGP Series enables it to outperform other mineral oil based lubricants.

## Application

Natural gas compressor

## Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	NGP-68	NGP-100	NGP-150	NGP-220
Article number	340218	340081	340082	340083
Density	0.867 g/cm <sup>3</sup>	0.86 g/cm <sup>3</sup>	0.874 g/cm <sup>3</sup>	0.871 g/cm <sup>3</sup>
Flash point	243 °C	246 °C	241 °C	246 °C
Kinematic viscosity, 100°C	10.0 mm <sup>2</sup> /s	13.1 mm <sup>2</sup> /s	18.6 mm <sup>2</sup> /s	26.3 mm <sup>2</sup> /s
Kinematic viscosity, 40°C	67.0 mm <sup>2</sup> /s	95.0 mm <sup>2</sup> /s	150 mm <sup>2</sup> /s	218 mm <sup>2</sup> /s
Viscosity index	137	136	140	154
Pour point	-33 °C	-32 °C	-32 °C	-32 °C
Four-ball tester: wear characteristics	0.51 mm	0.56 mm	0.58 mm	0.52 mm

# NGP® Series

Natural gas compressor lubricant



Characteristics	NGP-68	NGP-100	NGP-150	NGP-220
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months	36 months	36 months	36 months

Characteristics	NGP-320
Article number	340291
Density	0.872 g/cm <sup>3</sup>
Flash point	100 °C
Kinematic viscosity, 100°C	35.3 mm <sup>2</sup> /s
Kinematic viscosity, 40°C	325 mm <sup>2</sup> /s
Viscosity index	154
Pour point	-34 °C
Four-ball tester: wear characteristics	0.65 mm
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

## Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /  
9010 County Road 2120, Tyler, TX 75707 /  
Phone: +1 800 749 5823 / [www.klsummit.com](http://www.klsummit.com)

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.